

Living Shoreline Case Study

Delaware City Refinery, Delaware City

Chris Pfeifer, Integral Consulting

Project Details

Goals:

- Shoreline Position
- Habitat

Energy Environment:

- High (1-6 mile fetch)
Wind-driven waves especially storms
Wakes from commercial boat traffic

Construction Dates:

- September 2015 (5 working days)

Partners:

- Delaware City Refining Company LLC
- Living Shorelines Solutions Inc. (LSS)
- Cardno, Inc.

See the Site Before and After

Pre-installation September 2015



Post-installation October 2020



Baseline Conditions

June 2014

Severely eroding shoreline along



Baseline Conditions

Issues:

- Ongoing shoreline erosion threatened critical infrastructure servicing the refinery's dock area including roads, pipelines, and fire-fighting stations
- Shoreline retreat averaged ~2.3ft. per year (2007 -2013) with higher annual loss rates in years with hurricanes and nor'easters

Site Characteristics/Important Features to Consider:

- Design must be resilient; capable of accommodating sea level rise (+50 years)
- Compatible with port operations including maintenance dredging of nearby ship berths and permanent booming for oil spill response
- Aesthetics not a driving consideration
- Construction access required heavy-lift cranes to move machinery and materials over active pipelines

Living Shoreline Installation

Design Elements:



- Wave Attenuation Devices (WADs[®])

Permitting:

- State—Delaware Individual Subaqueous Lands Permit
- Federal—Army Corps of Engineers Section 404 Individual Permit

Materials and Placement:

- WADs[®] are proprietary 3-sided, pyramid-shaped, pre-cast concrete structures with openings (baffles) on each facet to dissipate wave energy
- WADs[®] for this project were manufactured at local concrete plant using molds leased from product developer (LSS) and hauled to site on flatbed trailer
- Hydrodynamic modeling used to refine WAD[®] dimensions and deployment configuration
- ~500 WADs[®] arranged along 1,450 linear feet of eroding shoreline in overlapping double-row parallel to shore just above MLW
- WADs[®] placed offshore using crane or amphibious excavator



Monitoring Efforts

| Metric | Method |
|----------------------------|-------------------------|
| Shoreline position | Cross Sections (RTK) |
| Sediment accretion | Coring/Grain Size |
| Habitat | Vegetated edge (GPS) |
| Habitat | Wildlife (Visual/Photo) |
| WAD [®] Stability | Visual/Photo/GPS |
| Major Weather | Event Log |


Measured Environmental Results

- Passive accretion/retention of fine-grained silt and clay sediments along protected shoreline
- 1.9ft. average increase in bottom elevation landward of WADs[®] within 3 years
- Marsh vegetation expanding to colonize new sediment deposits
- No settling or shifting of WADs[®] observed to date
- WADs[®] did not deter wildlife use
- First project to use WAD[®] technology in Delaware River Basin (demonstration project)

Adaptive Management/Lessons Learned

Design Elements

- Need to lift equipment/materials over pipelines during construction added complexity/cost
- Accretion monitoring hampered by low bearing capacity of newly deposited sediments
- Value of hydrodynamic modeling during design to avoid costly post-construction reconfiguration
- Shoreline energy reduction and passive accretion from WADs eliminated need for shoreline augmentation using dredge material



September 2015
Placement of WADs[®] with amphibious excavator



September 2015
Wave energy reduction landward of WAD[®] array

